

MEEETING GO CC600

All in one Conference Camera



4X
Lens

(360°)
Panoramic

Voice 
Tracking

5m 
Pickup Radius

One-Tap
Display modes

USB
plug & play

360° all-in-one conference camera integrates with camera, speaker, and voice-tracking microphone in a portable and stylish design. This camera provides you a vivid face-to-face meeting experience by delivering high definition video and crystal clear audio. Combining 360° camera, omnidirectional microphone and full duplex speaker in an affordable package, it offers the features of auto framing and voice tracking that are unique at a budget price range. Plug & play and compatible with a variety of video conference platforms, it provides an easy-to-use, high-quality audio and video solution for remote conferencing in huddle rooms.

High Definition CMOS Sensor

Crystal clear image with resolution up to 1080p@30fps, built in 4x lenses, each is with 2.1Mega pixel, deliver you vivid video images.

Compact Portability

As portable as your cell phone

One-touch Mute

One-tap Display Mode Switching

LED Voice Location Indicator



360° Panoramic View

360° Omnidirectional coverage with minimal distortion. Its omnidirectional & up-to 5 meters radius voice pickup capacity means you can host up to 10 participants.

AI Tracking with Auto Framing

Adopt advanced intelligent algorithm technology which recognizes and highlights the active speakers. (A green frame shows the active speaker). The camera automatically adjusts to keep participants centered smoothly.



Supporting One-tap Display Mode Switching | 6 varied display modes

Easy switch display modes for different presentation scenarios by touching the mode button.

1. Panorama Mode ; 2. Top and Down Mode ; 3. Composed Mode ; 4. Speaker 1 Mode ; 5. Speaker 2 Mode ; 6. Panning Mode.



USB Plug & Play

It is easy to start a meeting in a simple way. Plug in the power and USB cable anytime, anywhere, and you can start a video conference. The portable and compact design make it portable, not to miss any important meeting on the way.



MeetingGo CC600

Item Name:	MeetingGo CC600	Stitching Technology:	Dynamic Real + Time Stitching Technology
Model No.:	Tevo-CC600	Resolution:	Input: 4992x928 / 30fps Output: 1920x1080 / 30fps"
Image Sensor:	1/2.7" CMOS Sensor	Modes:	Compose / Focus / Grid / Body fit / Speaker / Top-Down
Max Frate Rate:	2592H x 1944V @30fps 10 bits	Tools:	Lighting : 0 - 100; 3D NR : 0 - 100; Gamma : 0 - 100; EV Adjust : -2 ~ +2; Flicker : Auto, 50Hz / 60Hz; Reset : Reset to Factory Setting High resolution, low distortion; Flexible screen layout with hardware dynamic ROI crop; AI & Beam Forming integration; Mute Button (Touch SW); Mode Select Button, (Switch H/W Image Output Mode and DOA Function)
Lens Construction:	5 Layer of Glass + IIRCF Elements	Advantages:	5M
Effective Pixels:	5.0 Megapixels	Button:	Yes
Focal Length:	f=2.49mm	Pickup Range:	200 Hz to 8k Hz
Aperture:	F2.5	Acoustic Echo Cancellation:	3W (mono)
Field of View:	140° (D), 140° (H), 103° (V)	Response Frequency :	Sound Playback Frequency Range : 200 Hz to 10k Hz
Hardware Out:	4992x928@30fps (Panorama Only) 1920x1080@30fps, 1280x720@30fps, 640x360@fps(Panorama, Top Down,Panning) DOA: Direction of Arrival	Rating Power:	Physical Interfaces:
Video Format	MJPEG / YUV2	Sound Playback Frequency Range :	DC In : DC Jack Φ2.5mm TYPE-C (USB 2.0)
Field of View:	Horizontal: 360° / Vertical 60° FOV Top: Vertical + 45° up / - 15° down FOV Middle: Vertical ± 30° FOV-Down: Vertical + 20° up / -40° down"	Operating Environment:	Temperature : 0 to 40 °C / Humidity : 10 to 90%
IQ Effect:	Lighting : 0 - 100; 3D NR : 0 - 100; Gamma : 0 - 100; Flicker : Auto , 50Hz / 60Hz; Reset : Reset to Factory Setting	System Requirements:	Windows: OS: Windows: 7, 10 64 bit Recommended to use Intel 7th generation i5 or above (or equivalent), RAM 4GB or above; MAC: OS: 10.15 ↑ Recommended to use Mac mini i3 (2018) or above (or equivalent), RAM 8GB or above
Features:	Adaptive ROI; People Tracking; Beamforming Tracking	Size:	67.5mm x 67.5mm x 182.3mm
Microphone Array:	Built-in 4 Digital Microphones Unidirectional Microphones	Weight:	447g(net weight)
Far-Field Voice Capture:	Support	Notice:	Above listed Conferencing Software, Brand owners need to get the certification by themselves
Beamforming:	Yes		
Speaker:	Full-Range Speaker x 1		
Sound Pressure:	70db ↑ (@1m at : pink noise 0dB)		
LED Display:	Circularity 12*2 Blue LED Indicators / Touch Button Display RGB colors		
Maximum Power Consumption:	< 8W		
UVC / UAC Version:	1.1 / 1.0		
Compatible Software:	Can be used in video conferencing software that supports UVC Cameras Zoom, Cisco Webex, Google Meet, Skype, Microsoft Teams and more.		

Hotline : 400-1080-686
Tel : 0086-755-8526-1373
Email : sales01@tenveo.com
Address : A-1st Floor, B-8th Floor, Fukang Keji Mansion, Yousong Road,
Fukang Community, Longhua Dist., ShenZhen, China

